

5315 -380KV									
Props	KV	Throttle	Voltage	Current	Thrust	RPM	Power	Efficiency	OperatingTemperature
HQ15X7-3	380	10%	24.00	0.3	51	881	8.04	6.30	62℃
		20%	23.99	1.1	232	1808	25.33	9.18	
		30%	23.98	2.35	520	2676	56.31	9.23	
		40%	23.96	4.38	894	3489	104.94	8.52	
		50%	23.94	8.24	1433	4394	197.24	7.26	
		60%	23.90	13.54	2056	5234	323.51	6.36	
		70%	23.86	20.59	2782	6043	491.18	5.66	
		80%	23.79	30.04	3627	6824	714.58	5.08	
		90%	23.71	41.50	4504	7560	983.97	4.58	
		100%	23.65	55.29	5422	8266	1307.54	4.15	
HQ15X7-3	380	10%	32.00	0.4	81	1115	11.84	6.88	62℃
		20%	31.99	1.3	377	2311	41.65	9.05	
		30%	31.98	3.24	855	3446	103.55	8.25	
		40%	31.96	6.48	1482	4492	206.94	7.16	
		50%	31.92	12.40	2364	5598	395.65	5.97	
		60%	31.87	20.61	3343	6638	656.90	5.09	
		70%	31.81	31.87	4502	7636	1013.75	4.44	
		80%	31.69	49.56	5976	8687	1570.49	3.81	
		90%	31.55	70.57	7409	9521	2226.58	3.33	
		100%	31.41	94.98	8768	10233	2983.16	2.94	
GF1308-3	380	10%	32	0.36	38.95	1117	11.52	3.38	71℃
		20%	31.99	1.11	217.75	2378	35.51	6.13	
		30%	31.98	2.432	521.91	3578	77.78	6.71	
		40%	31.97	4.498	917.14	4687	143.80	6.38	
		50%	31.95	8.101	1468.01	5893	258.83	5.67	
		60%	31.92	13.087	2113.34	6998	417.74	5.06	
		70%	31.87	19.97	2891.65	8108	636.44	4.54	
		80%	31.82	30.557	3884.21	9313	972.32	3.99	
		90%	31.74	42.237	4809.52	10294	1340.60	3.59	
		100%	31.63	56.802	5848.57	11283	1796.65	3.26	
GF1308-3	380	10%	45.99	0.406	84.63	1550	18.67	4.53	71℃
		20%	45.99	1.478	440.04	3296	67.97	6.47	
		30%	45.98	3.595	1005.95	4906	165.30	6.09	
		40%	45.96	7.196	1757.5	6429	330.73	5.31	
		50%	45.93	13.193	2757.74	7939	605.95	4.55	
		60%	45.86	24.657	4197.07	9665	1130.77	3.71	
		70%	45.76	37.565	5598.56	11073	1718.97	3.26	
		80%	45.63	56.86	7266.12	12447	2594.52	2.80	
		90%	45.46	84.792	8823.77	13566	3854.64	2.29	
		100%	41.79	101.875	9034.27	13751	4257.36	2.12	